



SERIES RKN & RKN-V


RIBBON WIRE

FOR AUTOMATIC BONDERS



Available Vertical Hole Ø marked with X

	TD		TDF		For Vertical Hole
	in.	mm	in.	mm	
1/16	.0624	1.59	.0460	1.17	
1/16	.0624	1.59	.0590	1.50	X
	.0784	1.99	.0630	1.60	
	.0784	1.99	.0720	1.83	X
3/32	.0937	2.38	.0880	2.24	X
	.1180	3.00	.0985	2.50	
1/8	.1249	3.17	.0937	2.38	
1/8	.1249	3.17	.1180	3.00	



We recommend a .0005" back radius and a cross groove or a flat bond foot when ordering tools for gold wire thermosonic bonding. For more gold wire application information see **Tech Tip**



RKN-V SERIES VERTICAL FEED DEEP ACCESS

RKN-SERIES RIBBON WIRE

Ribbon Width: .0020" through .030"
Ribbon Thickness: .00025" through .0020"

For all large Ø

Ribbon Width: .0020" through .030", Ribbon Thickness: .00025" through .0020"




NOTE: We recommend our A8D option for enhanced wire control. Our standard vertical feed has slightly more clearance but less wire control. See Tool Option for illustration. To order just add A8D in space 12.

A8D Option
available for ribbon widths up to .005

Hole Angle	BSV	
	in.	mm
45°	.035	.89
52°	.050	1.27

Standard: Ø 1/16, 45° to 52° Hole Angle : BS"=.045" (1.14mm) .
Supplies only to Standard size Ø1/16, larger tool Ø are different.
Standard: (BS) supplied unless otherwise specified. See Tool Options #A3

Standard: Ø1/16 45° to 52° Hole Angle :
BS"=.045" (1.14mm)
Standard: (BS) supplied unless otherwise specified. See Tool Options
No Front Angle if T=MAX



SERIES RKN & RKN-V

RIBBON WIRE

ORDERING INFORMATION

RIBBON BONDING WEDGES

FOR GOLD AND ALUMINUM WIRE

SAMPLE PART NUMBER: M-RKN-O-D-1/16-1-45-CG-.5x5-2-M-*

SYMBOL EXPLANATION: 1 2 3 4 5 6 7 8 9 10 11 12

1. **MATERIAL:** _____
 M = Ceramic
 C = Tungsten Carbide
 T = Titanium
 All other: See Material Selection Guide
2. **SERIES:** RKN _____
3. **WIRE FEED:** O = Standard Feed _____
 V = Vertical Feed _____
4. **FRONT/BACK RADIUS:** See Radius Option Chart
 *For special Radius sizes insert an X Please specify FR/BR
5. **SHANK DIA.:** Please Specify Diameter _____
6. **TOOL LENGTH:** Please Specify Length _____
7. **HOLE ANGLE:** for RKN (30°, 38°, 45°, 52°, 55°, 60,°) for RKN-V (45°, 55°, 60,°)
 for RKN-V with A8D Opt.(45°, 52°)
- (12) See Tool Option
- (11) **FOOT FINISH:**
 M = Matte finish (FR, BR, & Bond Flat)
 P = Polish finish (FR, BR, & Bond Flat)
 MP= Polish finish (FR, BR), and Matte finish (Bond Flat)
- (10) **Bond Length:** See Standard Chart
 Example: BL of .0020 = 2
 Note: We do not recommend bond lengths any larger than .005".
- (9) **RIBBON SIZE:** See Standard Chart
 Example: .0005 x .005 = .5 x 5
 Thickness x Width
- (8) **FOOT TYPE:** F = Flat
 CG = Cross Groove
 DT = Diamond Tip
 (Please specify Ribbon size)

For special sizes or dimensions insert an (X) in the appropriate position of the part number then specify what (X) equals. Example: M-RKN-O-X-1/16-3/4-45-CG-.5x5-2-M-A7 (X) FR=.0012, BR=.0007

RADIUS OPTION CHART	OPTION LETTER		A	B	C	D	E	F	G	H	I	J	K	L	M	N
	FRONT RADIUS	in.	.0005	.0005	.0010	.0010	.0010	.0015	.0015	.0015	.0015	.0020	.0020	.0020	.0020	.0020
	BACK RADIUS	in.	0	.0005	0	.0005	.0010	0	.0005	.0010	.0015	0	.0005	.0010	.0015	.0020
		μ	0	13	0	13	25	0	13	25	38	0	13	25	38	51

For Vertical Feed: Tmax. for Dia. 1/16 = .0190 and for A8D: Tmax=.0243, Supplies only to Standard size Ø1/16, larger tool Ø are different.

Size Restrictions for Vertical Feed Tools		
STANDARD		
TD	Maximum Ribbon Width	Maximum "T" Dimension
1/16	.0150	.0190
3/32	.0300	.0210
A8D Option, RW up to .0070		
TD	Maximum Ribbon Width	Maximum "T" Dimension
1/16	.0070	.0243
A8D Option, RW .0080 and larger		
TD	Maximum Ribbon Width	Maximum "T" Dimension
1/16	.0120	.0190
Larger Tool Ø, Ribbon Width and "T" Dimensions available upon request		
RW = Ribbon Width		

STANDARD CHART		RKN		FOR RIBBON THICKNESS: .00025" THROUGH .0020"											
				WIDTHS: .002" THROUGH .030"											
RIBBON WIDTH	RIBBON THICKNESS	BL		T(30°38°)		T(45° 52°)		T(55° 60°)		W					
in.	μ	in.	μ	in.	μ	in.	μ	in.	μ	in.	μ	in.	μ		
Tolerance				±.0002	±5	±.0005	±13	±.0005	±13	±.0005	±13	±.0005	±13	±.0002	±5
.0020	51	through .00125	6.4 32	.0010	25	.0130	330	.0110	279	.0090	229	.0055	140		
				.0015	38	.0130	330	.0120	305	.0090	229				
				.0020	51	.0130	330	.0120	305	.0090	229				
				.0025	64	.0140	356	.0120	305	.0100	254				
.0030	76	through .00125	6.4 32	.0010	25	.0160	406	.0130	330	.0100	254	.0065	165		
				.0015	38	.0170	432	.0140	356	.0100	254				
				.0020	51	.0170	432	.0140	356	.0110	279				
				.0025	64	.0180	457	.0150	381	.0110	279				
.0040	102	through .00125	6.4 32	.0030	76	.0180	457	.0155	394	.0120	305	.0075	191		
				.0020	51	.0170	432	.0140	356	.0110	279				
				.0025	64	.0180	457	.0150	381	.0110	279				
				.0030	76	.0180	457	.0155	394	.0120	305				
.0050	127	through .0020	13 51	.0020	51	.0170	432	.0140	356	.0110	279	.0085	216		
				.0025	64	.0180	457	.0150	381	.0110	279				
				.0030	76	.0180	457	.0155	394	.0120	305				
				.0035	89	.0190	483	.0160	406	.0120	305				
.0070	178	through .0020	13 51	.0025	64	.0180	457	.0150	381	.0110	279	.0125	318		
				.0030	76	.0180	457	.0155	394	.0120	305				
				.0035	89	.0190	483	.0160	406	.0120	305				
				.0040	102	.0195	495	.0160	406	.0130	330				
.0100	254	through .0020	13 51	.0025	64	.0180	457	.0150	381	.0110	279	.0155	394		
				.0030	76	.0180	457	.0155	394	.0120	305				
				.0035	89	.0190	483	.0155	394	.0120	305				
				.0040	102	.0195	495	.0160	406	.0130	330				
.0120	305	through .0020	13 51	.0025	64	.0180	457	.0150	381	.0110	279	.0175	445		
				.0030	76	.0180	457	.0155	394	.0120	305				
				.0035	89	.0190	483	.0160	406	.0120	305				
				.0040	102	.0195	495	.0160	406	.0130	330				
.0150	381	through .0020	13 51	.0025	64	.0180	457	.0150	381	.0110	279	.0205	521		
				.0030	76	.0180	457	.0155	394	.0120	305				
				.0035	89	.0190	483	.0160	406	.0120	305				
				.0040	102	.0195	495	.0160	406	.0130	330				
.0200	508	through .0020	13 51	.0025	64	.0180	457	.0150	381	.0110	279	.0255	648		
				.0030	76	.0180	457	.0155	394	.0120	305				
				.0035	89	.0190	483	.0160	406	.0120	305				
				.0040	102	.0195	495	.0160	406	.0130	330				

*Other sizes available upon request *All dimensions and tolerances are for reference only
 "T" To be determined according to the size of FR and BR and Hole Bore Length